RTC Products Overview

	EIRE GO ST 173	IMBIO B 1837		
	AM0805	AM0815	AM1805	AM1815
	< 14nA with RC	< 14nA with RC	< 14nA with RC	< 14nA with RC
	oscillator	oscillator	oscillator	oscillator
Liltra Law Sunnly Current	< 22nA with RC oscillator and	< 22nA with RC oscillator and	< 22nA with RC oscillator and	< 22nA with RC oscillator and
Ultra-Low Supply Current	autocalibration	autocalibration	autocalibration	autocalibration
	< 55nA with crystal	< 55nA with crystal	< 55nA with crystal	< 55nA with crystal
	oscillator	oscillator	oscillator	oscillator
Baseline Timekeeping				
Crystal (XT) Oscillator	✓	✓	✓	✓
Number of GP Outputs	4	3	4	3
Advanced Timekeeping				
RC Oscillator	✓	✓	✓	✓
Calibration/Auto-calibration	✓	✓	✓	✓
Watchdog timer (WDT)	~	✓	~	~
RAM (Bytes)	256	256	256	256
Enhanced I/O and Power Management				
VBAT Switch	✓	✓	~	✓
External Interrupts	~	~	~	
Reset Management	-	-	~	~
Power Switch and Sleep Finite State Machine (FSM)	-	-		
Programmable Charging Current	-	- 	✓	✓
Interface	I ² C up to 400kHz	3/4-wire SPI up to 2MHZ	I ² C up to 400kHz	3/4-wire SPI up to 2MHZ
Wide Operating Range				
Operating Voltage	1.5-3.6V	1.5-3.6V	1.5-3.6V	1.5-3.6V
Operating Temperature	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C
Package Option	3 mm x 3 mm 16-pin QFN package	3 mm x 3 mm 16-pin QFN package	3 mm x 3 mm 16-pin QFN package (also available in wafer form)	3 mm x 3 mm 16-pin QFN package (also available in wafer form)
Ordering Information	AM0805AQAM1805I2CEVB(EVB)	AM0815AQAM1815SPIEVB(EVB)	AM1805AQAM1805I2CEVB(EVB)	AM1815AQAM1815SPIEVB(EVB)